



NO	J1	J1-NC	J2
1	GND	YD	GND
2	VDD	LP	VDD
3	V0	XSCL	V0
4	/WR	M	A0
5	/RD	V0	/WR
6	/CS	VDD	/RD
7	A0	GND	DB0
8	/RES	VOUT	DB1
9	DB0	DO	DB2
10	DB1	D1	DB3
11	DB2	D2	DB4
12	DB3	D3	DB5
13	DB4	DISPOFF	DB6
14	DB5	BLA	DB7
15	DB6	/CS	/RES
16	DB7	/RES	
17	BLA	VOUT	
18	VOUT	BLA	
19	BLA		
20	BLK		

Specification:

- 1). Driving: Duty:1/240, Bias:1/16,VLCD.23.0V,VDD:5.0V
- 2). Viewing angle: 6 O'clock
- 3). Display mode: STN/Negative/Transmissive/BLUE
- 4). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 5). IC: RA8835 (or compatible)
- 6). Backlight: EDGE WHITE
- 7). Dimensions with mark "*" are important, with mark "()" are referenced
- 8). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE
A0	First issue	1-14



深圳市三元晶液晶显示科技有限公司
Shenzhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. 模组型号	SYG320240C2V50-5C2BLN3R8-B5N1F-25	GENERAL TOL: ±0.3 未注公差
APPROVED BY	CHECKED BY	PAGE: 1 OF 1 UNIT: mm
DRAWING BY	PROJECTION 三 角 法	